

M-FIRE FOCUS EX Zone 0

PHH0213

ANSI/FL1 compliant



Ex-ATEX certified battery flashlight with magnetic switch and lockout function

Cree® XP-G2 LED / 235 lm / 4 x AA / 11 h 10 min

ANSI/FL1	100%	25%
	11 h 10 min	36 h
	235 lm	62 lm
	116 m	
	IP67	

Mactronic presents performance parameters according to the international ANSI/FL1 standards. The listed values were determined during specialized, laboratory tests of our products. To read more about ANSI standards go [here](#).

	184 x 52 x 52 mm
	152 g
	247 g
	15 g
	100% - SPOT 116 m / FLOOD 26 m 25% - SPOT 72 m / FLOOD 16 m



The kit contains a holder and clothing / work harness clip



Optional accessories:



Gallet helmet mounting
PHH0012M



Kalisz helmet mounting
RHH0041



I M 1 Ex ia I Ma II 1 G Ex ia IIC T4 Ga
DEMKO 15 ATEX 1476X

The set includes: batteries AA, key, clip, handstrap

Firefighters and professionals requiring reliable lighting to perform their courageous jobs in hazardous locations depend on the M-Fire 03 intrinsically safe [Ex ATEX] flashlight. To prevent sparks generated by an accidental opening, a screw secures the flashlight's head. A built-in pressure valve releases heat, keeping the flashlight's internal parts from dangerously overheating. Despite its helmet-friendly lightweight, the M-Fire 03 is shock, dust and water resistant boasting an IP68 ANSI rating. A magnetic switch easily engages the light's 157 lms. A safety lock prevents battery drainage while in transport, ensuring the M-Fire 03's 13-hour operation time is always available when needed.