

SW34 - Leather Welding Jacket

Collection: Safewelder

Range: Flame Resistant Multi-Norm

Shell Fabric: Split Cowhide Leather, thickness 1.3 mm

Outer Carton: 10

Product information

This premium quality welding jacket is made from split cowhide leather and stitched with para-aramid thread. It offers enhanced protection to the torso when welding and is designed to last in the toughest environments.

Safewelder

Safewelder is made using premium split cowhide leather and stitched with para-aramid thread. Designed to last in the toughest environments, this collection offers enhanced protection when welding.

Flame Resistant Multi-Norm

This industry leading flame resistant range provides multi-standard protection for hazardous environments. These state of the art products are the result of years of experience combined with advanced technology and market research. Commitment to the health, safety and comfort of the wearer can be seen in the wide range of products suitable for all climates and end uses.

Standards

EN ISO 11611 Class 2 (A1)



Features

- Made with cowhide leather for a premium finish
- Class 2 welding protection
- Internal pocket for safe storage
- Adjustable waist for a perfect fit
- Concealed hook and loop fastening for easy closure
- Hook and loop cuffs for a secure fit
- Designed to be worn in a tough work environment
- CE certified
- UKCA marked

SW34 - Leather Welding Jacket

Commodity Code: 4203100000

Test House

Intertek Italia S.p.A. (Notified Body No.: NB: 2575)

Via Guido Miglioli 2/A,

-, Italy

Cert No: ITASLNB23013526

Wash Care

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m ³)	EAN13	GTIN/DUN14
SW34TARS	Tan	43.0	28.0	60.0	1.4200	0.0722	5036108373857	25036108858334
SW34TARM	Tan	43.0	28.0	60.0	1.4400	0.0722	5036108322343	25036108811117
SW34TARL	Tan	43.0	28.0	60.0	1.5600	0.0722	5036108322336	25036108811100
SW34TARXL	Tan	43.0	28.0	60.0	1.5900	0.0722	5036108322350	25036108811124
SW34TARXXL	Tan	43.0	28.0	60.0	1.7700	0.0722	5036108322367	25036108811131
SW34TARXXXL	Tan	43.0	28.0	60.0	1.9600	0.0722	5036108322374	25036108811148